



DRAWING CHANGES

REV	ECN NO	DESCRIPTION	BY	CKD	DATE

TANK

DRY WEIGHT: 250L - 60kg
 315L - 72kg
WET WEIGHT: 250L - 310kg
 315L - 385kg
SYSTEM WEIGHT: 190kg

HD200 HEATERS:
 GAS LOAD EACH 200MJ
 - NG 1.13 - 2.75 kPa
 - LPG 2.75 kPa
 FAN ASSISTED , BALANCED FLUE
 WEIGHT 20kg EACH APPROX

THERMOSTAT:
 FACTORY SET AT 65°

PRIMARY PUMP:
 DD6: 2xGRUNDFOS UP25-80B
 WITH WEATHER PROOF COVER

GENERAL NOTE:
 TANK REQUIRES EXTERNAL
 GPO. PRIMARY PUMP CONNECTS
 INTO TANK GPO.

CONTACT RINNAI COMMERCIAL FOR CIRCULATION DESIGN

HOT WATER OUTLETS
TEMPER AS REQD

SINGLE & DUAL
CIRCULATION
PUMPS OPTIONAL
(NOT INCLUDED)
GPO'S REQUIRED

ISOLATION VALVES
GPO REQD
PER HEATER
20mm RISERS
32mm MANIFOLD

STRAINER
COLD EXPANSION VALVE
PRESSURE LIMITING VALVE
NON RETURN VALVE
ISOLATION VALVE

NOT INCLUDED

COLD WATER
INLET

850 kPa PTR
VALVES

COMBO TANK

32mm
CONNECTORS

32mm
CONNECTORS

OPTIONAL BASE

375 375 375 375 375

WALL

2250

SERVICE SPACE

3325

MATERIAL	DRAWN	DAP
TOLERANCE - UNLESS STATED	DATE	21/05/12
0.±1.0 0.0 ±0.5	CHECKED	SVL
0.00 ±0.1 Angular ±1	APPROVED	
FINISH:	DO NOT SCALE DRAWING	

Rinnai Australia Pty Ltd

**DEMAND DUO-DD6200E
STORAGE HOT WATER**

Weight	Drawing Number(PART NO)	Revision
	RA-21-05-12-010	