



Rinnai

Rinnai TX Series

Designed for Australia's ever-changing climate, the Rinnai TX Series delivers reliable heating and cooling all year round. With built-in Wi-Fi and voice control, you can easily manage your comfort through the **NetHome Plus app** or compatible devices. The new HEPA filtration system helps create a healthier home environment by removing dust particles and reducing bacteria in the air you breathe.

Smart by design

For over 50 years, Rinnai has supplied Australian homes with a range of appliances that help people lead comfortable, safe and efficient lifestyles. The TX Series range boasts a sleek and contoured, white matte finish indoor unit.



New Ultimate Control

Take comfort to the next level with inbuilt Wi-Fi and voice control to manage your favourite settings via the NetHome Plus app, and compatible Google Assistant or Amazon Alexa devices.*



New Healthier Indoor Air

Equipped with a Cold Catalyst Filter and a HEPA Filter, it reduces up to 99%[^] of bacteria and dust particles, helping deliver cleaner, healthier indoor air for everyday comfort.



Superior Corrosion Protection

The Rinnai TX Series condenser coil is coated with our GoldGuard coating making it more resistant to oxidation and corrosion than ordinary condenser coils.



Inverter Technology

Delivers fast heating and cooling, with smart operation that maintains consistent temperatures and helps reduce running costs.



Quiet Operation

Designed to keep noise levels to a minimum without affecting performance, thanks to its clever design optimised to deliver better air distribution.



3D Airflow

Air blades can be controlled to swing both horizontally and vertically, allowing for balanced room temperature and comfort.



Dehumidifying Mode

Efficiently manages room humidity levels to ensure optimum comfort levels during humid summer days.



Timer

A delay ON or OFF timer allows you to select a period of time (from 30 minutes to 24 hours), the unit will turn either on or off depending on its current status.



Sleep Mode

The TX Series intelligent sleep mode operates on a two-way temperature control that modulates up and down to mimic outside ambient temperatures, ensuring a comfortable sleep.



Demand Control

Equipped with Demand Response Enabling Device (DRED) to help reduce overall power consumption at critical peak load times.**



R32 Refrigerant

R32 refrigerant has lower Global Warming Potential (GWP) than traditional refrigerants. Additionally, it provides higher energy efficiency while using lower refrigerant volumes.



Turbo Function

Quickly cool in summer or swiftly warm in winter.

*For full details visit www.rinnai.com.au

~Tested by Intertek, Report No. 250626075GZU-007 and 250626075GZU-001, an independent third-party laboratory.

**Subject to availability from your energy provider.

*Rinnai uses a third-party application (App) to enhance your experience of the Rinnai product. You may use the App at your sole discretion. Please note that when you download and use the App and its services, the third-party's privacy policy and terms and conditions of service will apply. By using the Rinnai product through this App, you acknowledge and agree that: The third-party App may collect, store, and process your personal information according to its own privacy policy and App terms and conditions. Rinnai does not control and are not responsible for the content, policies, or practices of the third-party App and its services. Rinnai strongly recommends that you review the App privacy policy before using its features. The use of the third-party App is optional. For further information or clarification, please contact us at 1300 555 545 and privacy@rinnai.com.au

HSNRTX Series Wall-Mounted Split Air Conditioner Quick Selection Guide

EXPOSED ASPECT	FLOOR AREA SQUARE METRES (2.6m Ceiling) ▼	AVERAGE ASPECT	FLOOR AREA SQUARE METRES (2.6m Ceiling) ▼	PROTECTED ASPECT
<ul style="list-style-type: none"> • Strong afternoon sun, little or no external shade • Weatherboard, fibro or brick veneer walls • No ceiling insulation • Large or west facing windows • Little or no protection from the sun 		<ul style="list-style-type: none"> • North facing, some external shade • Brick veneer, or double brick • Ceiling insulation • Average size windows with some internal or external window shading 		<ul style="list-style-type: none"> • South facing aspect • Will have shaded walls and windows all year • Brick veneer or double brick • Ceiling insulation • Average size windows, little or no direct sun
INVERTER REVERSE CYCLE HIWALL SPLIT MODELS & NOMINAL kW RATING				
2.5 kW ▶	10	◀ 2.5 kW ▶	10	◀ 2.5 kW
	11		11	
	12		12	
	13		13	
3.5 kW ▶	14	◀ 2.5 kW ▶	14	◀ 2.5 kW
	15		15	
	16		16	
	17		17	
5.0 kW ▶	18	◀ 3.5 kW ▶	18	◀ 3.5 kW
	19		19	
	20		20	
	21		21	
6.0 kW ▶	22	◀ 5.0 kW ▶	22	◀ 5.0 kW
	23		23	
	24		24	
	25		25	
7.0 kW ▶	26	◀ 6.0 kW ▶	26	◀ 6.0 kW
	27		27	
	28		28	
	29		29	
8.0 kW ▶	30	◀ 7.0 kW ▶	30	◀ 7.0 kW
	31		31	
	32		32	
	33		33	
9.0 kW ▶	34	◀ 8.0 kW ▶	34	◀ 8.0 kW
	35		35	
	36		36	
	37		37	
RECOMMEND A LARGER CAPACITY SYSTEM, E.G. RINNAI DUCTED AIR CONDITIONING SYSTEM	38	◀ 9.0 kW ▶	38	◀ 9.0 kW
	39		39	
	40		40	
	41		41	
	42	RECOMMEND A LARGER CAPACITY SYSTEM, E.G. RINNAI DUCTED AIR CONDITIONING SYSTEM	42	RECOMMEND A LARGER CAPACITY SYSTEM, E.G. RINNAI DUCTED AIR CONDITIONING SYSTEM
	43		43	
	44		44	
	45		45	
	46	◀ 9.0 kW ▶	46	◀ 9.0 kW
	47		47	
	48		48	
	49		49	
	50	◀ 8.0 kW ▶	50	◀ 8.0 kW
	51		51	
	52		52	
	53		53	
	54	◀ 7.0 kW ▶	54	◀ 7.0 kW
	55		55	
	56		56	
	57		57	
	58	◀ 6.0 kW ▶	58	◀ 6.0 kW
	59		59	
	60		60	
	61		61	
	62	◀ 5.0 kW ▶	62	◀ 5.0 kW
	63		63	
	64		64	
	65		65	
	66	◀ 3.5 kW ▶	66	◀ 3.5 kW
	67		67	
	68		68	
	69		69	
	70	◀ 2.5 kW ▶	70	◀ 2.5 kW
	71		71	
	72		72	
	73		73	
	74	◀ 2.5 kW ▶	74	◀ 2.5 kW
	75		75	
	76		76	
	77		77	
	78		78	

This guide has been developed to cover most normal situations. If unusual or abnormal conditions apply, a full heat load survey should be conducted.