

# Features and Benefits



## Star Rating

High efficiency 5.6 stars.



## Design

Sleek and modern design to suit contemporary homes.



## Warranty <sup>(3)</sup> <sup>(4)</sup>

Class leading warranty of 3 years parts and labour and 10 years heat exchanger.



## Delivery Temperature

10 litres per minute of hot water @ 25°C rise. <sup>(1)</sup>



## Connectability

NG or LPG available.



## Stability Temperature

Puretemp® water delivery technology inbuilt to provide a perfectly constant outlet water temperature.



## Safety

Heat shield included.



## Retrofit Prepared

Water and gas connections placed for quick and easy changeover.



## Battery Ignition

No power required and ideal for remote locations.



## Flow Rate

Minimum flow rate of 2.9 litres per minute. Maximum flow rate 13 litres per minute<sup>(2)</sup>



## Confidence

Reliable in high wind conditions.



## Support

Backed by Rinnai's national service network.

### Technical Information - Model FM10NA or FM10LA

Width (mm)	380
Depth (mm)	219
Height (mm)	838
Weight (kg)	14
Flow rate (@ 25°C rise)	10 L/min
Set temp	60°
Gas Consumption (MJ/h)	76.2 / 76
Star rating	5.6
Min inlet water pressure (kPa)	120
Max inlet water pressure (kPa)	1000
Ignition source	D cell battery (Supplied)

### Plumbing Connections

Hot & Cold	R 1/2" (13mm)
Gas - NG (regulator kit supplied)	R 3/4" (20mm)
Gas - LP (regulator kit supplied)	R 1/2" (13mm)

Disclaimer: (1) Based on 15°C inlet water temperatures. (2) Delivery temperature is reduced at maximum flow rate. (3) The models in this table are unsuitable for solar hot water applications. Any failure or service issue when installed in a solar hot water application is not covered by warranty. (4) These models must not be installed in areas where the temperature remains below 0°C for extended periods. Frost failures are not covered by warranty.