

System Selection

Description	System	Tank Size	Booster	N° of Tubes	Boost Capacity	STC Zones ⁽¹⁾				
						1	2	3	4	
Rinnai Sunmaster										
Split System Gas	50	175L	S20	20	20L/min	26	29	25	22	
	51	175L	S26	20	26L/min	26	29	25	22	
	52	175L	S20	25	20L/min	29	32	29	26	
	53	175L	S26	25	26L/min	29	32	29	26	
	54	215L	S20	25	20L/min	30	32	30	26	
	55	215L	S26	25	26L/min	30	32	30	26	
	56	270L	S26	25	26L/min	29	31	29	26	
	61	270L	S26	30	26L/min	38	42	36	32	
Split System Electric	64	320L	S26	30	26L/min	38	42	36	32	
	57M	250L	3.6kW	25	150	30	32	30	27	
	57B	250L	3.6kW	25	250L	28	29	27	23	
	58M	315L	3.6kW	25	170	30	32	30	26	
	58B	315L	3.6kW	25	315L	28	28	26	23	
Split System Gas	59M	315L	3.6kW	30	170	38	42	36	32	
	Rinnai Prestige									
	Split System Gas	N	250L	S20	25	20L/min	34	39	32	28
		P	250L	S26	25	26L/min	34	39	32	28
R		315L	S26	25	26L/min	31	32	30	27	
S		315L	S26	30	26L/min	38	42	37	32	
Split System Electric	TM	250L	3.6 kW	25	165L	31	32	30	26	
	VM	315L	3.6 kW	25	185L	30	32	29	25	
	WM	315L	3.6 kW	30	185L	32	33	32	29	

⁽¹⁾ STC's are subject to change. See www.cleanenergyregulator.gov.au for conditions and qualifications.
For more information on warranty conditions and exclusions download our booklet from www.rinnai.com.au

With our policy of continuous improvement, we reserve the right to change, or discontinue at any time, specifications or designs without notice.
Note: All images contained within this brochure are for illustrative purposes only, the colours and finishes of the products featured are as close to the respective product range as photographic lighting and printing processes allow.

Rinnai Australia Pty Ltd

ABN 74 005 138 769

100 Atlantic Drive,
Keysborough, Victoria 3173

For further information
call 1300 555 545 or visit
rinnai.com.au

TOTAL HOME COMFORT



Rinnai