

Technical Information

		Hotflo 25L	Hotflo 50L	Hotflo 80L	Hotflo 125L	Hotflo 160L	Hotflo 250L	Hotflo 315L	Hotflo 400L	Hotflo 160L Compact
Model Series		HFE					EHFA			
Storage Capacity (L)		33	55	84	140	172	279	334	420	170
Hot Water Delivery (L)		25	50	80	125	160	250	315	400	160
Element Size (kW)		1.8, 2.4, 3.6	1.8, 2.4, 3.6	1.8, 2.4, 3.6	1.8, 2.4, 3.6	1.8, 2.4, 3.6	2.4, 3.6, 4.8	2.4, 3.6, 4.8	3.6, 4.8	2.4,3.6
Total Height (mm)	Α	452	694	900	1245	1620	1477	1770	1840	1313
Width incl. PTR Valve (mm)		490	490	590	590	564	674	674	744	600
Diameter (mm)	В	415	415	515	515	500	605	605	675	537
Outlet Height (mm)	С	297	524	685	1020	1419	1248	1541	1587	1107
Inlet Height (mm)	D	153	158	225	225	162	210	210	237	186
Electrical Entry - Lower (mm)	Е	80	80	155	155	87	135	135	163	110
Electrical Entry - Upper (mm)	F	N/A	N/A	N/A	N/A	1039	985	1225	1263	N/A
Packaged Weight (kg)		23	29	48	60	60	70	82	96	56
Boost Capacity (Twin element only) (L)		N/A	N/A	N/A	N/A	40	50	60	81	N/A
Included PTR Valve (kPa)						1000				
ECV (kPa)		850								
Max. Inlet Pressure with ECV (kPa)		680								
PLV with ECV (kPa)		500								
Max. Inlet Pressure without ECV (kPa)		800								
PLV without ECV (kPa)		500								
Max. Thermostat Setting (°C)						70				
Ingress Protection Rating						IPX4				
Electrical Supply						240V - @50Hz				
Hot and cold water connection						Rp 3/4 (20mm)				
Tank Body Colour		Wh	nite				Dune			





In accordance with our policy of continuous improvement, Rinnai Australia reserves the right to make modifications, change specifications or discontinue models at any time without notice, however, we will endeavour to communicate major changes before implementation. Dimensions are subject to production tolerances and may vary slightly from those given. For full definitions of domestic and commercial use along with the full warranty conditions and exclusions, please refer to the owners manual. The images reproduced in this brochure are for illustrative purposes only, are not to scale and may vary in colour to those of the represented product.