Rinnai



Ducted Air Conditioning



Rinnai Ducted Air Conditioning

Experience complete comfort all year round with the Rinnai Ducted Reverse Cycle Inverter System (DRCi). It conditions the entire home through insulated duct work, providing rapid cooling and heating with excellent dehumidification, all while filtering the air as it is dispersed to each room. Condition your whole home, or zone specific rooms/spaces to suit your lifestyle, without having to install individual units on your walls.

Incorporating the latest DC Inverter technology, the Rinnai DRCi System is a cost effective solution when compared with conventional Air Conditioners. Its flexibility means it can be installed in both new and existing homes.











At Rinnai, we're all about comfort

For over 50 years, Rinnai has supplied Australian homes with a range of appliances that help people lead comfortable, safe and efficient lifestyles.

Being driven to create comfort means that we really care about our products and your experience from start to finish. We're focused on developing products with the latest technology and our level of quality is second-to-none, so you can rest assured knowing Rinnai will deliver.

A new world of comfort

Features and Benefits

All-In-One Total Home Comfort

The Rinnai DRCi is built to withstand some of Australia's harshest conditions. Its ability to cool at temperates ranging outside from -15°C to 50°C and heat at -15°C to 24°C, allows for total home comfort no matter where you live.

Features such as auto restart function in case of an electrical power outage provides you with peace of mind. The innovative DC Inverter varies its speed in order to maintain a consistent temperature which suits your home and its conditions.

All of this without the hassle of having to install multiple units saves you space, time and money.

Flexible Design

With its slim indoor design, air outlets can be installed in the ceiling to utilise the best available space. The design of the system also suits a range of applications from narrow rooms to more accommodating spaces.





Heating & Cooling

All year round comfort, with full temperature control suited to your needs.



Wi-Fi Control

Set your favourite temperature from anywhere, with our intuitive Android or Apple App. Come home to ultimate comfort.



Fast Temperature Control

Combination of control mechanisms constantly monitor the system operating conditions to maintain your chosen temperatures.

3D DC synchronisation technology, ensures a fast and controlled warm up and cool down while delivering effective energy conservation.



Quiet Operation

Designed to keep noise levels to a minimum without affecting performance, thanks to the efficient indoor/outdoor fans and DC inverter compressor.

Fans slow down when the outside temperature falls, making them even quieter.

Programmable Controllers Indoor Fan Coil Unit (Installed within roof space Outdoor Condensing Unit

Illustrative purposes only





Slimline Design

As the indoor fan coil unit is concealed in the roof, all you'll see in your home is the discreet ceiling diffusers and Controller.

Speak to your installer about which diffusers best compliment your living spaces.



Programmable Controller

The Rinnai DRCi system may be configured to a Programmable Controller or Rinnai Home, both are optional accessories.



Reduced Operational Costs

3 times more energy efficient than conventional electric heating. It also complies with the Australian Government's Minimum Energy Performance Standards (MEPS) and is rated to Australian Standard AS-3283.3.



Zoning Option

Choose to cool or heat your entire home at once, or zone specific areas to your pre-selected levels of comfort. Consult with your specialist dealer for a zone control option that suits your specific application and lifestyle.

Comfort at the touch of a button

Rinnai Home Zone Controller

Wi-Fi Control

The Rinnai DRCi features optional Wi-Fi control via an App.

Simple to activate and easy to use, the App can be downloaded via Google Play or the App Store on a compatible mobile device. Once installed and registered, you can operate your appliance on the go.


Basic functions like on/off, temperature control and fan speed can be accessed through the App. Best of all, the Wi-Fi control allows you to switch on your Air Conditioner from outside the home – creating the ultimate in convenience and comfort.

We're at your service

The National Customer Care Centre provides first class service and maintenance of your system, ensuring it's running at its highest efficiency - so you can enjoy the Rinnai experience for many years to come.

Operating 5 days a week (Monday to Friday)





Turn your Air Conditioner on or off,


set your temperature, fan speed and

more remotely from anywhere in the world with an internet connection.

normal remote controller.



• <u>·</u>



Set your favourite temperature before you come home - enjoy the

Available to download via:

- Google Play
- App Store

Get in the zone

Put an end to arguments over the perfect temperature. The Rinnai Home controller can control up to 8 zones that can be configured using a touch screen controller and wireless sensors.

Fan Auto Control

Rinnai Home automatically adjusts your system's fan speed according to how many zones or rooms are actively being cooled. More smart energy savings. No effort required.*

Active Temperature Management

Rinnai Home's intelligent sensors will redirect cooled air from one room to another, so rooms reach their set temperature as quickly and efficiently as possible.

Fine-tuned lifestyle favourites

You use your home in different ways on different days, so create up to nine favourite programs to suit your routine. Switch rooms or zones on or off. Do it manually or automatically, on a timer.

13 43 73



Stay in control

Rinnai Home Features and Benefits

Control your Air Conditioning System from your smart device

The Rinnai Home Controller offers precise and easy climate control so you can immerse yourself into total home comfort. You'll also benefit from the unparalleled energy efficiency and savings.

The Rinnai Home climate control system is highly affordable, efficient and effective. It lets you control your air conditioning using your smart device so the whole family can come home to the perfect temperature. The Rinnai Home Controller is the perfect addition whether you're installing a new air-conditioning system, or retrofitting an old one.

Make fine adjustments automatic With wireless wall sensors, Rinnai Home monitors and maintains the temperature in real time, in every zone, automatically adjusting the airflow when each room hits your ideal temperature.





Rinnai Home Controller

A typical installation will consist of one touch controller (maximum of 3) controlling one zone while the remaining zones are managed by wireless sensors (maximum of 8).

- Whole-of-home 8" touch screen
- Climate control up to 8 zones
- Available in black or white
- Fan Auto Control*
- Active Temperature Management

Rinnai Wireless Sensors

- Temperature
- Zone Control sensor
- Available in black or white
- Turn ON/OFF in Climate control

Rinnai Home Apps

Smart Features

- In duct supply air sensor for improved efficiency and temp control
- Dedicated zone sensor to ensure every zone is maintained at the exact temperature automatically
- Temperature sensor in every touchscreen controller
- Zone on/off button on every sensor
- Fan auto control to maximise comfort and minimise energy consumption
- All sensors can be calibrated for precision control

| \otimes | 8 zones | 8 | Zone temperature control |
|-----------|-----------------|---|--------------------------|
| 8 | AC Unit control | 8 | Favourites and schedules |

- ✓ Favourites and schedules
- ✓ WI-FI & Remote access Solution of the second second

- Up to 9 programmable favourite settings
- Convenient Timer
- Filter Clean reminder
- Schedule assistant

Integrate all your favourite lifestyle and entertainment apps - Google Home, Amazon Alexa and Apple Home Kit - for a seamless, voice-controlled smart home experience your whole family can enjoy.

Sleep timer

♂ 5% Airflow control adjustments

Technical Information

-

00 00

| | Rinnai - System Model No. | | 07 | 09 | 11 | 13 | 15 | 18 | |
|---|---|---|-----------------|------------------|----------------------|--------------------------|-------------------|----------------|--|
| Nominal Capao | city | kW | 7 | 9 | 11 | 13 | 15 | 18 | |
| Power Supply | (To Outdoor Unit) | V-Ph-Hz | | 220 - 24 | 0-1-50 | | | | |
| Maximum Input Power | | W | 3400 | 4600 | 4600 | 7000 | 7000 | 7000 | |
| Maximum Input Current | | | 16 | 21 | 21 | 31 | 31 | 31 | |
| Recommende | d Circuit Breaker Size | A | 20 | 25 | 25 | 32 | 32 | 32 | |
| Rated Capacity | | | 7.3 | 9.0 | 10.5 | 12.5 | 14 | 17 | |
| | Capacity Range | kW | 2.38~9.00 | 3.15~11.85 | 3.15~11.85 | 4.20-15.75 | 4.20-15.75 | 6.80-19.50 | |
| Cooling | Rated Input Power | W | 2100 | 2550 | 3100 | 3450 | 4200 | 5250 | |
| ocomig | Rated Input Current | A | 9.8 | 14.5 | 14.2 | 18.2 | 18.2 | 22.5 | |
| | AEER | W/W | 3.4 | 3.5 | 3.4 | 3.6 | 3.3 | 3.2 | |
| | Rated Capacity | | 7.5 | 10.0 | 11.5 | 13.0 | 14.5 | 18.0 | |
| | Capacity Range | kW | 1.79 - 10.5 | 3.45 - 13.50 | 3.45 - 13.50 | 4.44 - 16.65 | 4.44 - 16.65 | 6.90 - 21.10 | |
| I I a a b'ar a | | 14/ | | | | | | | |
| Heating | Rated Input Power | W | 1.7 | 2.25 | 2.7 | 3.15 | 3.6 | 4.55 | |
| | Rated Input Current | A | 7.9 | 12.8 | 12.8 | 16.3 | 16.3 | 19.5 | |
| | ACOP | W/W | 4.3 | 4.4 | 4.2 | 4.1 | 4.0 | 3.9 | |
| | Indoor Unit | | DINLR07B1 | DINLR09B1 | DINLR11B1 | DINLR13B1 | DINLR15B1 | DINLR18B | |
| Rated Input | | W | 90 | 250 | 560 | 560 | 560 | 420 | |
| Rate Current | | А | 1.6 | 2.5 | 2.5 | 3.0 | 3.0 | 3.0 | |
| Air Flow (With Filter) High Speed | | L/s | 480 (100Pa) | 625 (100Pa) | 710 (150Pa) | 1050 (150Pa) | 1050 (150Pa) | 1080 (150Pa | |
| Air Flow (Minimum) | | L/s | 140 | 190 | 190 | 250 | 250 | 410 | |
| Maximum External | | | | | | | | | |
| Static Pressure (ESP) | | Pa | 160 | 160 | 200 | 200 | 200 | 200 | |
| Noise Level | (Hi/Med/Lo)" | dB(A) | 38.5/35.5/32.5 | 45/42/39.5 | 39/37/34.5 | 46.5/43.5/40 | 46.5/43.5/40 | 53/49.5/45. | |
| | Net (W x D x H) | mm | 1100x774x249 | 1360x774x249 | 1200x625x380 | 1200x625x380 | 1200x625x380 | 1400x858x44 | |
| Dimensions | Packaging (W x D x H) | | 1305x805x315 | 1570x805x320 | 1485x675x450 | 1485x675x450 | 1485x675x450 | 1605x910x5 | |
| | Net / Gross Weight | kg | 32/38.5 | 40/48 | 53/62 | 53/62 | 53/62 | 81/92 | |
| | Supply Air (W x H) | | 926 x 175 | 1186 x 175 | 1000 x 253 | 1000 x 253 | 1000 x 253 | 1188 x 385 | |
| Duct Connecti | Return Air (W x H) | | 1001 x 228 | 1261 x 228 | 1145 x 334 | 1145 x 334 | 1145 x 334 | 1188 x 385 | |
| Condensate Drain Pipe Outer Diameter | | mm | 25 | | | | | | |
| Refrigerant Piping Liquid / Gas Connections | | | 9.5 /15.9 | 9.5 / 15.9 | 9.5 / 15.9 | 9.5 / 15.9 | 9.5 / 15.9 | 9.5 / 19.0 | |
| Moisture Removal | | L/h | 2 | 2.5 | 2.7 | 3.0 | 3.0 | 3.5 | |
| Controller | | Туре | | W | ired Programmable Co | ntroller with Wi-Fi Cont | rol | | |
| Operating Range | | °C | | | Cooling: 17 ~ 32 | , Heating: 0 ~ 30 | | | |
| | Outdoor Unit | | DONSR07B1 | DONSR09B1 | DONSR11B1 | DONSR13B1 | DONSR15B1 | DONSR18E | |
| Power Supply | | V-Ph-Hz | | | 220-240-1-50 | | | | |
| Starting Current | | А | 2.2 | 2.5 | 2.5 | 3.6 | 3.6 | 4 | |
| Compressor | | Туре | | | Twin Rotary | | | | |
| Sound Pressure Level @ 1m | | .,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,, | 60 | 60 | 62 | 60 | 60 | 60.5 | |
| Sound Power Level | | dB(A) | 65 | 68 | 68 | 69.5 | 69.5 | 72 | |
| Net (W × D × H) | | | 890 x 342 x 673 | 946 x 410 x 810 | 946 x 410 x 810 | 952 x 415 x 1333 | 952 x 415 x 1333 | 952 x 415 x 13 | |
| Dimensions | Packing (W × D × H) | mm | 995 x 398 x 730 | 1090 x 500 x 845 | 1090 x 500 x 845 | 1095 x 495 x 1380 | 1095 x 495 x 1380 | 1095 x 495 x 1 | |
| DIMENSIONS | Net / Gross weight | lum. | 45/48 | 70/75 | 70/75 | 95 / 110 | 95 / 110 | 96/111 | |
| | ů | kg | 437 46 | 10715 | | | 937110 | 907111 | |
| | Туре | | R32 | | | | | | |
| | Pre-Charged Length Charge Adjustment | mm g/m | 15m 24 | | | | | | |
| Refrigerant Piping | (Add or Remove) | - | 0.5.11.5.5 | 0.5.1.5.5 | 0.5 / | 0.5 / | 0.5 / | | |
| | Liquid / Gas Connections | mm | 9.5 /15.9 | 9.5 / 15.9 | 9.5 / 15.9 | 9.5 / 15.9 | 9.5 / 15.9 | 9.5 / 19.0 | |
| | Maximum Pipe Length | | 50 | 75 | 75 | 75 | 75 | 75 | |
| | Miniimum Pipe Length | mm | 3 | 3 | 3 | 3 | 3 | 3 | |
| | Maximum Vertical Separation Separation | | 25 | 30 | 30 | 30 | 30 | 30 | |
| | erature Limits | °C | | | Cooling-15~50 | Heating -20 ~ 24 | | | |

Capacities tested in accordance with AS/NZS 3823.3. With our policy of continuous improvement, we reserve the right to change, or discontinue at any time, specifications or designs without notice. Note: All images contained within this brochure are for illustrative purposes only, the colours and finishes of the products featured are as close to the respective product range as photographic lighting and printing processes allow.

Rinnai Australia Pty Ltd

ABN 74 005 138 769

100 Atlantic Drive, Keysborough, Victoria 3173

For further information call 1300 555 545 or visit rinnai.com.au

TOTAL HOME COMFORT







