# **Rinnai Black B26**

Builders Series Continuous Flow Hot Water



The Rinnai B26 Continuous Flow Hot Water system, available in a sleek black finish, delivers the same solid performance you can count on. Rinnai B26 50°C and 60°C natural gas units, available where you buy Rinnai nationwide.



#### **Quality Design**

Built with high-quality componentry, all housed in a compact, Japanese-designed and manufactured unit with a sleek black finish.



## 6-Star Efficiency

Superior 6-star efficiency for lower ongoing running costs.



### Water Conservation

Low flow shower head (WELS) compatible with 1.5L/minute minimum operating flow rate.



#### **Temperature Stability**

Puretemp<sup>™</sup> technology provides perfectly stable outlet water temperature.



## Built to Last

With 25 year heat exchanger warranty#.



#### **Connectability** 50°C compliant models available with quick connect systems for water controllers.











## **Technical Information**

| Model   | B26   |
|---|---|
| No. of Bathrooms (Cool Climate / Warm Climate)* | 1-2.5 / 1-3   |
| Installation                                    | External  |
| Gas Energy Rating                               | 6.0   |
| Heating Capacity L/Min (raised at 25°C)         | 26  |
| Height (mm)                                     | 531   |
| Width (mm)                                      | 351   |
| Depth (mm)                                      | 195   |
| Weight (kg)                                     | 15  |
| Gas Input (High)                                | 199MJ/h   |
| Cold Water Connection (mm)                      | 20 (3/4")   |
| Hot Water Connection (mm)                       | 20 (3/4")   |
| Gas Connection (mm)                             | 20 (3/4")   |
| Minimum Operating Flow (L/Min)                  | 1.5   |
| Factory Pre-set Temperature (°C)**              | 50/60   |
| Colour  | Black   |
| Ignition  | Direct electronic ignition with automatic flame sensing                                   |
| GasType   | NG  |
| Electrical Supply                               | AC 240V 50 Hz (10 amp weatherproof power point)   |
| Water Controllers                               | Up to 4 Water Controllers can be installed  |
| Heat Exchanger Warranty                         | 25 Years#   |
| Parts and Labour Warranty                       | 3 Years (5 Years if two or more Water Controllers are installed in domestic applications) |

\* Sizing assumes AAA or 3 star outlets. Half a bathroom refers to a guest shower or powder room that is not used all of the time. For more sizing information, consult with your hot water specialist. \*\* 50°C appliances can be adjusted up to 53°C. For 60°C plus installations a tempering valve in accordance with AS3500.4 is required. # Made from premium materials and built to last, Rinnai provides a standard 3 year (12 Year Heat Exchanger) parts and labour warranty on all Builders Series Continuous Flow hot water systems, plus an optional 13 years extended Heat Exchanger warranty. Visit rinnai.com.au for full terms and conditions.

With our policy of continuous improvement, we reserve the right to change, or discontinue at any time, specifications or designs without notice. Note: All images contained within this brochure are for illustrative purposes only, the colours and finishes of the products featured are as close to the respective product range as photographic lighting and printing processes allow.

